

H-1 Group Office Files

possible future reference.

H-1

August 16, 1954

Carl W. Buckland, Leader, General Monitoring Section; -H-1 ATOMEC ENERGY COMMISSION

CONTAMINATION LEVELS ON J-DIVISION TRAILERS

Location

Collection

It seems that three longshoremen involved in unloading four J-Division trailers at the San Francisco docks have claimed they received beta burns. The four trailers are identified as J-13-1, J-13-2, J-15-2 and J-15-3. The levels detected by army personnel from group J-4 and from H-1 personnel have been recorded herewith for the purpose of

I. Col. John W. Lipp and Sgt. Joseph J. Guyette of Group J-4 monitored the four tradlers in San Francisco priorto their departure for Los Alamos. Their findings are as follows:

	Max. Surface	5 feet from Fromt End	12 feet from Sides	Cab of <u>Tractor</u>
J-13-1	20. mr/hr	3. mr/hr	.3 mr/hr	.2 mr/hr
J-13-2	21. "	1. "	.3 & .6 mr/hr	-
J-15-2	22. "	6. "	.5 mr/hr	-
J-15 - 3	15. "	5. "	.9 "	-

The survey was made with a Beckman MX-5 open shield GM instrument. Col. Lipp assured me that the meters were in good condition as they had just been serviced by the medical group (I assume this to be NRDL) and that to his knowledge no saturation took place.

Film badges worn by personnel accompanying the trailers received no exposure.

II. H-1 was called to SM-30 to spot survey the trailers prior to unloading. A maximum of 70 mrep/hr, shield open, cutie pie reading was obtained on a ladder at contact. The most active swipe was 3 to 5 mr/hr as read with a 263B Victoreen, shield open. The commercial tractors had been released without a survey. It was not felt necessary to tail the tractors due to the low level swipes, especially in the vicinity of the tractor hitch and the fact that all trailers had been steam cleaned prior to leaving the islands.

BEST COPY AVAILABLE



H-1 was later approached by Howard Buffington of J-13 to further decontaminate J-13-1, 2, 3 and 4 trailers prior to factory reconditioning. At the request of Leo Chelius, trailers J-13-1 and 2, and J-15-2 and 3 were to be monitored thoroughly prior to decontamination due to the San Francisco developments. The maximum values and pertinent data are listed in the accompanying table. As many as 200 readings were recorded in detail for each trailer and are recorded on the attached work sheets.

Readings tabulated as 20.+ mr/hr in some instances mean that the activity was greater than what could be read with an open shield GM instrument but less than what could be detected with a cutie pie type.

The "cutie pie" type meter used was an open window Reychronix. Model Dl.

The persons who did the monitoring at one time or another were Robert Elliott, James M. Oakes, Felix Vigil, Bruce Riebe, and Jose B. Romero.

CARL W. BUCKLAND

CWB/ed

cc: H-1 Grp. Ofc. file
H-1 Gen'l Monitoring Section file

Table attached.

COPIED DOE





					0	
	mr/hr	5.0	8. 00	o 	.1 to .5 toward front	
•	Max. Swipe mr/hr	Zero closed	.6 9.6	3 to 5 0	3 to 5 0	
t in mr/hr with a 263B Victoreen 0-Shield Open	Bottom	1.8 C 20. 0	1. 4.	.3 6.	1.5 C	•
	Back	.5 c 25. 0	μ. α 50. ο	.2 0	3.0	
	Front	8. c 55. o	8°.09	5. c	6. c 50. o	
count in	Left Side	15. c 55. o	5. c	1. c 25. 0	10.5 0	
Max. Surface Count in	R'Rht Side	20. c	7.5 C 70. 0	1.5 6	1. C	
Max. S	Top	7. c 25. 0	14. C	7 · C	9.0	

2 J CO ATOMIC INCR**CY**COMMERCION RG