

# **SANDIA REPORT**

SAND98-1240

Unlimited Release

Printed June 1998

## **Computational Methods for Predicting the Response of Critical As-Built Infrastructure to Dynamic Loads (Architectural Surety)**

D. S. Preece, J. R. Weatherby, S. W. Attaway, J. W. Swegle, R. V. Matalucci

**Prepared by**

**Sandia National Laboratories**

Albuquerque, New Mexico 87185 and Livermore, California 94550

Sandia is a multiprogram laboratory operated by Sandia Corporation, a Lockheed Martin Company, for the United States Department of Energy under Contract DE-AC04-94AL85000.

Approved for public release; further dissemination unlimited.



**Sandia National Laboratories**

Issued by Sandia National Laboratories, operated for the United States Department of Energy by Sandia Corporation.

**NOTICE:** This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government, any agency thereof, or any of their contractors or subcontractors. The views and opinions expressed herein do not necessarily state or reflect those of the United States Government, any agency thereof, or any of their contractors.

Printed in the United States of America. This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from  
Office of Scientific and Technical Information  
P.O. Box 62  
Oak Ridge, TN 37831

Prices available from (615) 576-8401, FTS 626-8401

Available to the public from  
National Technical Information Service  
U.S. Department of Commerce  
5285 Port Royal Rd  
Springfield, VA 22161

NTIS price codes  
Printed copy: A03  
Microfiche copy: A01



SAND98-1240  
Unlimited Release  
Printed June 1998

# **Computational Methods for Predicting the Response of Critical As-Built Infrastructure to Dynamic Loads (Architectural Surety)**

D. S. Preece<sup>1</sup>, J. R. Weatherby<sup>2</sup>, S. W. Attaway<sup>3</sup>, J. W. Swegle<sup>3</sup>, R. V. Matalucci<sup>4</sup>

<sup>1</sup>Geoscience and Geotechnology Center

<sup>2</sup>Computational/Computer Sciences & Math Center

<sup>3</sup>Engineering Sciences Center

<sup>4</sup>Security Systems and Technology Center

Sandia National Laboratories  
P. O. Box 5800  
Albuquerque, New Mexico 87185-0834

## **Abstract**

Coupled blast-structural computational simulations using supercomputer capabilities will significantly advance the understanding of how complex structures respond under dynamic loads caused by explosives and earthquakes, an understanding with application to the surety of both federal and nonfederal buildings. Simulation of the effects of explosives on structures is a challenge because the explosive response can best be simulated using Eulerian computational techniques and structural behavior is best modeled using Lagrangian methods. Due to the different methodologies of the two computational techniques and code architecture requirements, they are usually implemented in different computer programs. Explosive and structure modeling in two different codes make it difficult or next to impossible to do coupled explosive/structure interaction simulations.

Sandia National Laboratories has developed two techniques for solving this problem. The first is called Smoothed Particle Hydrodynamics (SPH), a relatively new gridless method comparable to Eulerian, that is especially suited for treating liquids and

gases such as those produced by an explosive. The SPH capability has been fully implemented into the transient dynamics finite element (Lagrangian) codes PRONTO-2D and -3D. A PRONTO-3D/SPH simulation of the effect of a blast on a protective-wall barrier is presented in this paper.

The second technique employed at Sandia National Laboratories uses a relatively new code called ALEGRA which is an ALE (Arbitrary Lagrangian-Eulerian) wave code with specific emphasis on large deformation and shock propagation. ALEGRA is capable of solving many shock-wave physics problems but it is especially suited for modeling problems involving the interaction of decoupled explosives with structures. In this study, ALEGRA has been employed in modeling a decoupled explosive in a tunnel with the explosive and surrounding air treated with Eulerian computational techniques and the tunnel liner and surrounding soil treated with Lagrangian computational techniques.

## **Acknowledgment**

The authors gratefully acknowledge the contribution of the team that performed the successful centrifuge experiment on a decoupled explosive in a tunnel. That team consisted of T. K. Blanchat, 6423; N. T. Davie, 9761; T. C. Togami, 9761; J. J. Calderone, 9761; R. A. Benham, 1553; B. D. Duggins, 1553; and D. E. Wackerbarth, 1553.

## Contents

Abstract .....	3
Acknowledgements .....	5
Contents .....	6
1.0 Introduction .....	9
2.0 Solid Wall Blast Simulation Using Smoothed Particle Hydrodynamics .....	10
3.0 Block Wall Blast Simulation Using Smoothed Particle Hydrodynamics .....	19
4.0 Design of Centrifuge Explosive Experiment Using Computer Simulations .....	25
4.1 LDRD Background .....	25
4.2 ALEGRA .....	25
4.3 Preliminary Calculations .....	25
4.4 Detailed Two-Dimensional Simulations .....	29
5.0 Conclusions .....	37
References .....	38

## Contents (continued)

### Figures

1. Wall and ground to be subjected to blast loading .....	12
2. Explosive and buffer zone SPH elements with wall and ground .....	13
3. Explosive, buffer zone, and air SPH particles with wall and ground .....	14
4. Pressure (psi) in SPH elements along with expansion and contact with wall. Air SPH elements are withheld from display .....	15
5. Pressure (psi) in the ground and wall induced by the explosive and air SPH particles .....	16
6. Velocity of wall perpendicular to wall induced by pressure loading .....	17
7. Wall displacement (inches) at 3.0 ms induced by pressure on wall .....	18
8. Displacement perpendicular to wall from the top to the bottom of the wall along the closest corner shown in Fig. 7 .....	18
9. Block wall and ground to be subjected to blast loading .....	20
10. Explosive and buffer zone SPH elements with block wall and ground .....	21
11. Pressure (psi) in SPH elements along with expansion and contact with block wall .....	22
12. Block wall deformation and motion at 5.8 ms .....	23
13. Zoom in on deformed block wall shown in Fig. 12 .....	24
14. Pseudo one-dimensional ALE model used to design the decoupled explosive tunnel experiment .....	30
15. Two-dimensional ALE model used to predict the response of the model to a decoupled explosive in a tunnel .....	31
16. Two-dimensional Finite Element (ALE) model of explosive, air, aluminum and soil .....	32
17. Pressure (Pa) induced by the explosive at 1.0, 5.0, 8.0 and 12 $\mu$ s .....	33
18. Pressure (Pa) induced by the explosive at 14, 19, 21, and 29 $\mu$ s .....	34
19. Pressure (pa) induced by the explosive at 100, 150, 200, and 245 $\mu$ s .....	35
20. Final deformed shape predicted for the aluminum tube .....	36

# Contents (continued)

## Tables

1. JWL Equation-of-State Parameters for PBX-9407 . . . . .	26
2. Soil and crushable foam constitutive model parameters for engineered soil . . . . .	26
3. Pressure versus volumetric strain for engineered soil . . . . .	27
4. Elastic-perfectly-plastic constitutive parameters for aluminum tube . . . . .	27
5. Ideal gas parameters for air . . . . .	28



## **1. Introduction**

The new and emerging threats to the infrastructure faced by today's engineering design and facility management community demand solutions that are innovative and increasingly based on engineering science and risk management approaches. There is a growing awareness of public vulnerability in the wake of bombings at the World Trade Center, the Oklahoma City Federal Building, and the Khobar Towers military barracks in Saudi Arabia; global civil and ethnic unrest; criminal violence and political terrorism; recent devastating natural disasters; and other indicators of a rapidly transforming social world. This awareness leads to increased expectations by the public and more demanding responsibilities for the professional involved in design, engineering, and construction of public facilities. The destruction that follows such natural disasters as hurricanes, tornadoes, floods, fires, and earthquakes underscores the need for enhanced structural safety, security, and reliability to protect the public from potential injuries, death, and heavy property losses.

A multidisciplinary Architectural Surety Program has been developed at Sandia National Laboratories to address the application of safety, security, and reliability concepts and technology products to the many critical national issues involved in the area of multihazard mitigation. One of these applicable technology products is the modeling and simulation of building performance exposed to abnormal and malevolent environments. Computer simulation capabilities are the necessary and appropriate technologies to evaluate the response of complex structures, such as multistory buildings, when subjected to the variety of dynamic loads resulting from blast effects of explosive attacks or ground motions from earthquakes. To provide an adequate model simulation capability, it is necessary to modify as required, verify with actual data, and finally apply available coupled hydrocodes and structural dynamics codes to the analysis and design of federal buildings and facility systems that are or will be exposed to these abnormal and malevolent environments.

Through internal resources within the Laboratory Directed Research and Development (LDRD) Program, an Architectural Surety development effort was initiated and pursued to couple existing hydrocodes with existing structural dynamics codes. This effort was planned to evaluate the predictive capability using generic structures and typical explosive loads. After validating the coupled codes using test data, this predictive capability will assist with improved designs of new complex structures, give support to vulnerability assessment studies, guide the evaluation of alternative retrofits, and assist in the selection of the most cost-effective mitigation measures (such as stand-off distance, barrier walls, or other defensive techniques). The work to date provides positive evidence that the coupled codes are operational in the supercomputer at Sandia National

Laboratories. The next step is to perform a series of validation procedures using actual multistory structural test configurations and blast response data from a well-planned instrumentation system.

The U.S. Department of Energy has invested significant resources in the development of advanced computational mechanics codes and has performed research to understand phenomena and interactions between the transient dynamic response of structures and fluid-like materials. The Accelerated Strategic Computing Initiative (ASCI) program, with its emphasis on teraflops computers and parallel implementation of computer tools, has permitted the extension of this technology to high-fidelity, three-dimensional structural configurations. These new modeling and simulation techniques can provide a significant amount of information to make critical decisions about the impact of different threat levels, the effects of a variety of natural disasters, and the required enhancements to structures and facilities for life-safety concerns. The goal is to evaluate complex explosive interactions of catastrophic dynamic loads on structures. The work completed has addressed a significant portion of the previously recognized deficiencies. Completion and validation of the coupled code will provide a valuable tool to be used for architectural and infrastructure surety.

Work on two different corporate LDRDs is documented in this report. The first, sponsored through Division 5000 titled *Computational Methods for Predicting the Response of Critical As-Built Infrastructure to Dynamic Loads (Architectural Surety)*, the same title as this report. This LDRD sought to demonstrate the computational mechanics tools currently available at Sandia National Laboratories that can be adapted to modeling explosive/structure interaction. The second LDRD, sponsored through Division 9000 is titled *Development of Explosive Event Scale Model Testing Capability at Sandia's Large Scale Centrifuge Facility*. This LDRD sought to bring experimental and computational mechanics personnel together to address an issue that would be of national interest from an Architectural Surety perspective. A portion of that work is presented in this report because it is applicable to the scope of this LDRD. The latter LDRD is documented in much more detail in Blanchat et al. 1998.

## **2. Solid Wall Blast Simulation Using Smoothed Particle Hydrodynamics**

Figure 1 illustrates a three-dimensional finite element model of a wall that will be subjected to an explosive loading. The wall is 1 ft thick and 13 ft high. The base is unattached to the ground beneath. Elastic concrete material properties are used for the wall and the ground with no allowance for damage or breakage in this calculation. Smoothed Particle Hydrodynamics (SPH) elements, represented by spheres, are shown in Figure 2 with the inner block modeling the explosive and the outer

block serving as a buffer/transition zone between the explosive and the air. A JWL (Jones, Wilkins, Lee) equation-of-state is employed to model the explosive which is assumed to be 15352 lb of ANFO, separated from the wall by a six-ft gap. The air is modeled as an ideal gas. Figure 3 illustrates the SPH elements used to model the air between the explosive and the wall. Detonation of the explosive is modeled with a controlled burn based on the detonation velocity and point of initiation. Figure 4 shows the detonation of the explosive with its resulting pressure (psi) expansion and impact on the wall. Contact resolution between the SPH and finite elements results in a calculated explosive loading of the ground and wall. This loading results in the pressure (psi) pulse in the ground and wall as shown in Figure 5. The pressure applied to the wall causes the velocity (in./s) distribution illustrated in Figure 6. The pressure also produces a displacement (in.) of the wall at 3 ms, as displayed in Figure 7. The displacement of the closest corner of the wall (Figure 7) from the top to the bottom is given in Figure 8 for a number of different times, up to 3 ms. It is obvious from Figures 5 through 8 that the loading on this wall is concentrated on the lower right corner and that this corner will break off and move at high velocity. The remaining portion of the wall will move with significant velocity.




Figure 1. Wall and ground to be subjected to blast loading.




Figure 2. Explosive and buffer zone SPH elements with wall and ground.




Figure 3. Explosive, buffer zone, and air SPH particles with wall and ground




Figure 4. Pressure (psi) in SPH elements along with expansion and contact with wall. Air SPH elements withheld from display.




Figure 5. Pressure (psi) in the ground and wall induced by the explosive and air SPH particles.








Figure 6. Velocity (in./s) of wall perpendicular to wall induced by pressure loading.



### **3. Block Wall Blast Simulation Using Smoothed Particle Hydrodynamics**

Many structures of interest in Architectural Surety have walls constructed of cement-block or brick. The ability to analyze structures with these elements is of great interest. A calculation similar to that discussed in Section 2 has been performed that models a block wall rather than a solid wall, as shown in Figure 9. In this model each block contains a number of three-dimensional finite elements and thus is deformable. The exterior surface of each block is also a contact surface that can interact with every other block in the model to maintain geometric integrity as block collisions occur. The interaction of the blocks in this calculation is limited to friction. Modeling of mortar between blocks either as a tensile strength between blocks or explicitly with finite elements is a capability available in PRONTO-3D but is not utilized in this model. Figure 10 illustrates the explosive and explosive/air transition zone adjacent to the block wall. Figure 11 shows the detonation and expansion of the SPH particles used to model the explosive gases and the interaction of those gases with the block wall. The explosive dimensions, mass, equation-of-state, and location relative to the wall are identical to those employed in the solid wall model discussed earlier. Figures 12 and 13 illustrate the calculated response of the blocks to the explosive loading at 5.8 ms. The calculation was terminated at this point due to an error in the SPH particle contact algorithm. This error has since been corrected.




Figure 9. Block wall and ground to be subjected to blast loading




Figure 10. Explosive and buffer zone SPH elements with block wall and ground.




Figure 11. Pressure (psi) in SPH elements along with expansion and contact with block wall. Air SPH elements withheld from display.





Figure 12. Block wall deformation and motion at 5.8 ms.



TIME 5.804E-3




Figure 13. Zoom in on deformed block wall shown in Figure 12.



## **4.0 Design of Centrifuge Explosive Experiment Using Computer Simulations**

### **4.1 LDRD Background**

The LDRD, as originally written, proposed to perform gravity scaling of an explosive event in a steady-state acceleration environment available through centrifuge testing. Many different types of explosive events amenable to gravity scaling were available, including cratering; a scale model building with explosively induced; gravity driven progressive collapse; and tunnels in rock or soil subjected to decoupled explosive loading. After considerable discussion it was decided to focus on a decoupled explosion in a tunnel in an engineered soil. The engineered soil had been used in a previous study (Tieszen and Attaway 1996). This configuration was chosen because length scales directly with gravity on underground structures with regards to stress and deformation.

### **4.2 ALEGRA**

The computer code ALEGRA was used in this study to design the size and thickness of the aluminum tunnel liner and the decoupled explosive charge inside the tunnel. ALEGRA is an arbitrary Lagrangian-Eulerian (ALE) wave code with specific emphasis on large distortion and shock propagation. (Budge et al. 1997a; Budge et al. 1997b).

### **4.3 Preliminary Calculations**

Preliminary calculations were performed using a pseudo-one-dimensional ALEGRA model. This model treats the explosive, air, tunnel liner and soil as depicted in Figure 14. Computational cells or elements in this model are actually two-dimensional axisymmetric but the boundary conditions on the model constrain it to one-dimensional behavior such as that observed when a shock wave is transmitted lengthwise through a metal rod. A gravitational acceleration of 100 g in the negative x direction is applied to this model.

A JWL equation-of-state, with a programmed burn, was employed to model the PBX-9407 explosive detonation (Budge et al. 1997a). Parameters necessary to characterize the explosive behavior during detonation are given in Table 1.

A soil/compressible-foam constitutive model was used to model the engineered soil compacted around the aluminum pipe. The parameters pertinent to this material model are presented in Tables 2 and 3. Table 2 contains the single-value parameters associated with this model, and Table 3 shows the pressure versus volumetric strain relationship necessary for the model.

Table 1. JWL equation-of-state parameters for PBX-9407

Parameter	Value	Units
$\Upsilon$ (reference density)	1.62	$\text{g/cm}^3$
A	5.73187E12	$\text{dyne/cm}^2$
B	1.4639E11	$\text{dyne/cm}^2$
C	1.20E10	$\text{dyne/cm}^2$
$\omega$	0.32	
$R_1$	4.6	
$R_2$	1.4	
CJ pressure	2.65E11	$\text{dyne/cm}^2$
D (detonation velocity)	7.91E5	$\text{cm/s}$
CJ temperature	4962.0	$^\circ \text{Kelvin}$

Table 2. Soil and Crushable Foam Constitutive Model  
Parameters for Engineered Soil

Parameter	Value	Units
$\Upsilon$ (initial density)	1.393	$\text{g/cm}^3$
K (bulk modulus)	2.0E8	$\text{dyne/cm}^2$
G (shear modulus)	640.0	$\text{dyne/cm}^2$
$A_0$	5.51E5	
$A_1$	0.95	
$A_2$	0.0	
Fracture Pressure	-1.0E3	$\text{dyne/cm}^2$

**Table 3. Pressure Versus Volumetric Strain for Engineered Soil**

<b>Volumetric Strain (%)</b>	<b>Pressure (dyne/cm<sup>2</sup>)</b>
0.006	239240.0
0.02	478400.0
0.064	957600.0
0.114	1909800.0
0.2231	3495600.0
0.24	3826500.0
0.26	5743300.0
0.27	7653100.0
1.0	148580000.0
1.73	289506900.0

An elastic-perfectly-plastic constitutive model was employed to model the aluminum tube that served as the tunnel liner after the emplacement of the soil around the tube. The constitutive model parameters selected for aluminum are given in Table 4.

**Table 4. Elastic-Perfectly-Plastic Constitutive Parameters for Aluminum Tube**

<b>Parameter</b>	<b>Value</b>	<b>Units</b>
E (Youngs Modulus)	6.89E11	dyne/cm <sup>2</sup>
$\mu$ (Poisson's ratio)	0.334	
Yield stress	2.76E9	dyne/cm <sup>2</sup>
Hardening modulus	1.02E10	dyne/cm <sup>2</sup>
Beta	1.0	

The final material behavior model necessary for this simulation is for the air that decouples the explosive from the tunnel liner. This was treated as an ideal gas with parameters given in Table 5.

**Table 5: Ideal Gas Parameters for Air**

Parameter	Value	Units
$\rho_o$ (Reference density)	0.001225	g/cm <sup>3</sup>
$\gamma$	1.4	
$T_o$ (Reference temperature)	288.2	° Kelvin
$C_v$	0.7178E4	

Variables that could be adjusted in this model included explosive radius, tunnel radius, and tunnel liner thickness. A tunnel diameter of 1.5 in. was chosen based on the general physical dimensions of the existing centrifuge swing-arm that constrained the size of the container holding the tunnel experiment. The container was sized to be a cube 2 ft on each side. The 2 ft depth with the tunnel in the center dictated one foot of soil above and below the tunnel. Experience indicated that the tunnel diameter should be approximately one-tenth the length of the soil surrounding it to control the influence of the upper (free) surface and lower (fixed) surface. The tunnel diameter was thus set at 1.5 in. The experimental configuration chosen is depicted in Figure 15 which shows the explosive, tunnel liner, and soil as designed.

A steady-state acceleration environment of 100 g on the centrifuge produces the same stresses and deformations in the soil and tunnel as would be observed in a model with all lengths multiplied by 100. This model thus simulates a 150 in. (12.5 ft., 3.81 m) diameter tunnel buried 100 ft. (30.48 m) deep.

With tunnel diameter and depth-of-burial already determined, the two variables that could be adjusted in the experiment were explosive diameter and tunnel liner thickness. Experience indicated that the diameter of the explosive would be the most important explosive parameter influencing its' effect on the tunnel liner. This was proven later by both the two-dimensional calculations and the experiment itself.

It was decided that the criteria for controlling the combination of explosive diameter and tunnel liner thickness should be measurable plastic deformation of the tunnel liner resulting from explosive detonation inside the tunnel. The tunnel liner thickness and explosive diameter were both constrained by the commercially available sizes. A number of simulations were performed with several combinations of explosive diameter and tunnel thickness using ALEGRA and the pseudo one-dimensional model.

The best combination arrived at was a tunnel liner thickness of 0.083 in. (0.2108 cm) and an explosive diameter of 0.1875 in. of PBX-9407. The length of the explosive was set at 3.75 in. (9.525 cm), which resulted in a total explosive weight of 2.75 g.

#### 4.4 Detailed Two-Dimensional Simulations

All design parameters discussed above were employed in a more detailed two-dimensional axisymmetric model of the tunnel experiment on the centrifuge. A close-up of the two-dimensional axisymmetric ALE model is shown in Figure 16. In this model the explosive, aluminum and soil are located just as in the one-dimensional model of Figure 14. The material models for the explosive, air, aluminum, and soil used in the two-dimensional model are exactly the same as those given above for the pseudo- one-dimensional model. Detonation of the explosive is designated to occur along the line on the bottom of the explosive. This model also has a gravitational acceleration of 100 g in the negative x direction.

Pressure caused by the detonation of the explosive and the deformation of the aluminum liner from times 0.0 to 245  $\mu$ s is shown in Figures 17 through 19. In Figures 17 and 18 the pressure corresponding to black has been set at  $1.0\text{E}9$  dynes/cm<sup>2</sup>. Pressures greater than this value are also plotted as black. A number of very interesting phenomena can be observed in this series of figures. In Figure 17 at 5  $\mu$ s the air is being pushed ahead of the explosive gas because of the large density difference between the two. By 8  $\mu$ s the air has been compressed by the explosive gas against the aluminum liner and begins to rebound as illustrated at 12 and 14  $\mu$ s. At 19  $\mu$ s the air is reconverging in the center of the tube where the explosive was before detonation. Thus, the shock wave marking the separation between the air and explosive gas reverberates a number of times in the tube. The majority of the energy imparted to the tube resulting in plastic deformation is expended during the initial impact of the explosively induced shock wave on the aluminum tube. Plastic deformation of the tube can be seen starting as early as 8  $\mu$ s. Transmission of the explosively induced shock wave through the tunnel liner and into the soil is observed in Figure 19 where the plotting pressure range has been significantly reduced to highlight lower pressures. The final predicted deformed shape of the tube is shown in Figure 20. The tube flare is the same length as the explosive and the outward displacement is constant indicating that the pseudo one-dimensional ALEGRA model used for the design of this experiment is an acceptable approach. The final outward displacement predicted by the one-dimensional model was 0.24 cm compared with 0.14 cm calculated from the two-dimensional model. A preliminary experiment was done wherein the explosive charge was detonated inside a bare tube wrapped with rubber. The outward displacement of the tube in this experiment was 0.15 cm. More details concerning this centrifuge experiment and the numerical analyses can be found in Blanchat et al (1998).




Figure 14. Pseudo-one-dimensional ALE model used to design the decoupled explosive tunnel experiment.




Figure 15. Two-dimensional ALE model used to predict the response of the model to a decoupled explosive in a tunnel.




Figure 16. Two-Dimensional ALE model of explosive, air, aluminum, and soil






Figure 17. Pressure (Pa) induced by the explosive at 1.0, 5.0, 8.0, and 12  $\mu s$ .




Figure 18. Pressure (Pa) induced by the explosive at 14, 19, 21 and 29  $\mu s$ .




Figure 19. Pressure (Pa) induced by the explosive at 100, 150, 200, and 245  $\mu s$ . Note the difference in the pressure range to highlight the shock wave moving outward through the soil.




Figure 20. Final deformed shape predicted for the aluminum tube.

## **5.0 Conclusions**

This work has demonstrated that a significant capability exists at Sandia National Laboratories for performing coupled explosive/structure interaction calculations. Smoothed Particle Hydrodynamics (SPH) coupled with three-dimensional finite elements provides one capability that was demonstrated by calculating the explosive loading on both a solid and a block explosive barrier wall.

The ALE code ALEGRA has been demonstrated by simulating a decoupled explosive in a tunnel. This code was used to design a scaled centrifuge experiment and a detailed two-dimensional ALEGRA analysis was used to better understand the experiment and to validate numerical methods.

## References

Attaway, S. W., 1992, *Update of PRONTO 2D and PRONTO 3D Transient Solid Dynamics Program*, Sandia National Laboratories, SAND90-0102.

Blanchat, T. K., Davie, N. T., Calderone, T. C., Togami, T. C., Preece, D. S. Weatherby, J. R., and Benham, R. A., 1998, *Development of Explosive Event Scale Model Testing Capability at Sandia's Large Scale Centrifuge Facility*, SAND98-0270, Sandia National Laboratories.

Budge, K. G., Peery, J. S., Robinson, A. C., Summers, R. M., and Wong, M.K., 1997, *ALEGRA: User Input and Physics Descriptions*, In Preparation, Sandia National Laboratories.

Budge, K. G., Peery, J.S. Trucano, T.G. and Wong, M. K., 1997, *ALEGRA: Verification Test Suite*, In Preparation, Sandia National Laboratories.

Swegle, J. W., Attaway, S. W., Heinstein, M. W., Mello, F. J. and Hicks, D. L., 1994, *An Analysis of Smoothed Particle Hydrodynamics*, Sandia National Laboratories, SAND93-2513.

Tieszen, S. R. and Attaway, S. W., 1996, *Fuel Dispersion in High-Speed Aircraft / Soil Impact Scenarios*, SAND96-0105, Sandia National Laboratories, January.

**Distribution:**

A. Emin Aktan  
Drexel University  
Drexel Intelligent Infrastructure Institute  
Academic Building, Room 240  
33rd & Arch Street  
Philadelphia, PA 19104

George K. Anderson, Major General, USAF, MC  
Deputy Assistant Secretary of Defense  
Health Services Operations & Readiness  
The Pentagon, Room 3E336  
Washington, DC 20301-1200

Arlan Andrews  
Survival Technologies International LLC  
1009 Bradbury Drive SE  
Albuquerque, NM 87106

Graham Armer  
GA Consulting  
Westwood House  
Eaudyke, Friskney  
Lincolnshire, United Kingdom PE22 8NL

George Y. Baladi  
FCDSWA/FCTT  
1680 Texas Street  
Kirtland AFB, NM 87117-5669

Darrell Barker  
Wilfred Baker Engineering  
8700 Crownhill, Suite 310  
San Antonio, TX 78209

Robert Barnes  
Lester B. Knight & Associates, Inc.  
549 West Randolph St.  
Chicago, IL 60661

Bill Barringer  
1001 University Blvd. Suite 103  
Albuquerque, NM 87106

Melvin L. Basye  
Security Division  
Office of Federal Protective Service  
18th and F Streets N.W., Room 2341  
Washington, DC 20405

Lynne Beason  
Civil Engineering Department  
Texas A&M  
College Station, TX 77843

Wade Belcher  
Building Technology Division  
General Services Administration  
18th & F St., NW - Rm 3329  
Washington, DC 20405

David Boyd  
Director, Science & Technology  
National Institute of Justice  
633 Indiana Avenue N. W.  
Washington, DC 20531

Jimmie Bratton  
Applied Research Association, Inc.  
4300 San Mateo Blvd. NE  
Albuquerque, NM 87110

Paul Bryant  
Mitigation Directorate, FEMA  
500 C Street SW  
MT/HZ/RA  
Washington, DC 20472

David Coltharp  
Environmental Systems Division  
Waterways Experimental Station  
3909 Halls Ferry Rd.  
Vicksburg, MS 39180-6199

Louise K. Comfort  
Graduate School of Public and International Affairs  
3E01 Forbes Quadrangle/GSPIA  
University of Pittsburgh  
Pittsburgh, PA 15260

Edward J. Conrath  
Special Projects Branch  
U.S. Army Corps of Engineers  
Omaha Division  
Omaha, NE 68102-4978

Bob Cox  
Cox & Associates  
6180 Pine St.  
Pollock Pines, CA 95726



Paul Croce  
Factory Mutual Research Corp.  
1151 Boston-Providence Turnpike  
Norwood, MA 02062

Robert Crossno  
Crossno Engineering  
3409 Calle Del Monte  
Albuquerque, NM 87106

Joel K. Dietrich  
Director, Division of Architecture  
The University of Oklahoma  
830 Van Vleet Oval, Room 162  
Norman, OK 73019-0265

John P. Dismukes  
College of Engineering  
University of Toledo  
1016 Nitschke Hall  
Toledo, OH 43606-3390

George Doremus  
Parson Process Group, Inc.  
100 W. Walnut Street  
Pasadena, CA 91124

Clarence Edwards  
General Services Administration  
Office of Federal Protective Service  
1800 F Street N.W., Suite 2341  
Washington, DC 20405

Ata Elauf  
The Sabre Group  
4000 N. Mingo Rd.  
MD 459  
Tulsa, OK 74116-5020

Charles Farrar  
Los Alamos National Laboratory  
PO Box 1663, MS P946  
Los Alamos, NM 87545

Sean P. Foohey  
Deputy Director of Operations  
& Planning Division - FEMA  
500 C St. S. W.  
Washington, DC 20472

Norman J. Glover  
AEGIS Institute, Inc.  
271 Central Park West  
New York, NY 10024

Kent Goering  
Hard Target Defeat Program  
Defense Special Weapons Agency  
6801 Telegraph Rd.  
Alexandria, VA 22310

Hermann Gruenwald  
Director Design Research Center  
College of Architecture  
University of Oklahoma  
830 Van Vleet Oval, Room GH 214A  
Norman, OK 73019-0265

Peter Gurvin  
Building Design & Engineering  
Office of Foreign Buildings Operations  
U.S. Department of State  
P.O. Box 12248, Rosslyn Station  
Arlington, VA 22219

Bruce Hall  
Building Technology Division  
General Services Administration  
18th & F St., NW - Rm 3329  
Washington, DC 20405

Jerome Hall  
Department of Civil Engineering  
University of New Mexico  
209 Tapy Hall  
Albuquerque, NM 87131-1351

Rod Haraga  
City of Los Angeles, Bureau of Engineering  
650 South Spring Street, Suite 200  
Los Angeles, CA 90014

Tim Hasselman  
ACTA Inc.  
2790 Skypark Drive #310  
Torrance, CA 90505

Eve Hinman  
Hinman Consulting Engineers, Inc.  
4163 24th Street  
San Francisco, CA 94114

Jim Howard  
Southwestern Bell Telephone Company  
800 N Harvey, Room 102  
Oklahoma City, OK 73102

John Kelmelis  
U.S. Geological Survey  
500 National Center  
12201 Sunrise Valley Drive  
Reston, VA 20192

Malcolm P. Keown  
Environmental Systems Division  
Waterways Experimental Station  
3909 Halls Ferry Rd.  
Vicksburg, MS 39180-6199

Do Kim  
Institute for Business & Home Safety  
73 Tremont Street, Suite 510  
Boston, MA 02108-3910

Anne Kiremidjian  
Department of Engineering  
Stanford University  
Stanford, CA 94305-4020

Stuart L. Knoop  
Oudens & Knoop, Architects, P.C.  
2 Wisconsin Circle, Suite 820  
Chevy Chase, MD 20815-7003

Dick Ling  
Lawrence Livermore National Laboratories  
P.O. Box 808, L-654  
Livermore, CA 94550

Richard G. Little  
National Research Council  
National Academy of Science  
2001 Wisconsin Ave., Harris Rm 274  
Washington, DC 20418

Gabor Lorant  
Gabor Lorant Architect, Inc.  
2701 East Osborn, Suite 3  
Phoenix, AZ 85016

Jim MacCornack  
MacCornack Engineering  
2920 Carlisle NE  
Albuquerque, NM 87110

Arup Maji  
Department of Civil Engineering  
University of New Mexico  
Albuquerque, NM 87131-1351

Sue Mallonee  
Injury Prevention Service-0307  
Oklahoma State Department of Health  
1000 NE 10th Street  
Oklahoma City, OK 73117

Ronald J. Massa  
Lorrion Corporation  
44 Mall Road, Suite 2000  
Burlington, MA 01803

Jon Matalucci  
Arizona State University  
School of Architecture  
Tempe, AZ 85287-1605

Richard Meehan  
Stanford  
701 Welch Rd., Suite 1120  
Palo Alto, CA 94304

Gerald Meyers  
U.S. Department of Energy, EH-53  
19901 Germantown Rd  
Germantown, MD 20874

Doug Mitten  
Project Management Services, Inc.  
4 Courthouse Square  
Rockville, MD 20850

Naser Mostaghel  
Department of Civil Engineering  
University of Toledo  
Toledo, OH 43606-3390  
Peter Mote  
The Nevada Testing Institute  
Nevada Testing Institute  
755 East Flamingo Road, P.O. 19360  
Las Vegas, NV 89132

William Murray  
Failure Analysis Associates  
P.O. Box 3015  
Menlo Park, CA 94025

Priscilla P. Nelson  
Construction/Geo Technology/Structure  
Program Cluster  
National Science Foundation  
4201 Wilson Blvd., Room 505N  
Arlington, VA 22230

John Petkewich  
Office of Property Development, General Services Administration  
18th and F Streets  
Washington, DC 20405

Ronald Polivka  
EQE International, Inc.  
44 Montgomery St. Suite 3200  
San Francisco, CA 94104

Brian W. Randolph  
Department of Civil Engineering  
University of Toledo  
Toledo, OH 43606-3390

Darren Rice  
Hard Target Defeat Program  
Defense Special Weapons Agency  
6801 Telegraph Rd.  
Alexandria, VA 22310

Robert Rocheleau  
Merrick & Company  
4820 Basin NE  
Albuquerque, NM 87111

Van Romero  
Research and Economic Development Division  
NM Tech  
801 Leroy Place  
Socorro, NM 87801

Thornton Schwenk  
SAIC  
5125 Russell Drive, NW  
Albuquerque, NM 87114

Douglas Seemann  
FCDSWA/FCTT  
1680 Texas St. SE  
KAFB  
Albuquerque, NM 87117-5669

Sheryll Shariat  
Injury Prevention Service-0307  
Oklahoma State Department of Health  
1000 NE 10th Street  
Oklahoma City, OK 73117

Wendall Shingler  
Chief of Administrative Services Division  
U.S. Marshals Service  
600 Army-Navy Drive  
Arlington, Virginia 22202

Robert Smilowitz  
Weidlinger Associates  
375 Hudson Street  
New York, NY 10014-3656

Milton L. Smith  
Department of Industrial Engineering  
Texas Tech University  
Glass Research and Testing Laboratory  
Box 41023  
Lubbock, TX 79409-1023

Mukund Srinivasan  
Hart Consultant Group  
2425 Olympic Blvd., #670  
Santa Monica, CA 90404

Mike Stanley  
Energetic Materials Research and Testing Center  
NM Tech  
801 Leroy Place  
Socorro, NM 87801

J. D. Stevenson  
Case Western Reserve University  
Department of Civil Engineering  
10900 Eulid Ave.  
Cleveland, OH 44106

John Strothman  
Strothman/Associates, Inc.  
1555 Sherman Ave. #340  
Evanston, IL 60201

Norris Stubbs  
Department of Civil Engineering  
Texas A&M University  
College Station, TX 77843-3136

Barry Sullivan  
U.S. Marshals Service  
600 Army-Navy Drive  
Arlington, Virginia 22202

Doug Sunshine  
Hard Target Defeat Program  
Defense Special Weapons Agency  
6801 Telegraph Rd.  
Alexandria, VA 22310  
Harvey Sorgan  
Depository Trust Company  
55 Water St.  
23rd Floor  
New York, NY 10041

Beth Tubbs  
ICBO  
5360 Workman Mill Road  
Whittier, CA 90601

Carlos Ventura  
Civil Engineering Dept.  
University of British Columbia  
2324 Main Mall  
Vancouver  
British Columbia, Canada V6T 1Z4

Robert Vincent  
Health Promotion and Policy Analysis  
Oklahoma State Department of Health  
1000 NE 10th Street  
Oklahoma City, OK 73117

Robert Volland  
Deputy Associate Director, Mitigation  
FEMA  
500 C Street, S. W.  
Washington, DC 20472

Douglas Wehring  
Director, Protective Design Center  
U.S. Army Corps of Engineers  
Omaha District  
215 North 17th Street  
Omaha, NE 68102-4978

Dennis E. Wenger  
Director, Hazard Reduction & Recovery Center  
Texas A&M University  
College Station, TX 77843-3136

Robert W. Whalin  
Waterways Experiment Station  
U.S. Army Corps of Engineers  
3909 Halls Ferry Road  
Vicksburg, MS 39180-6199

Bill White  
Bechtel  
50 Beale Street  
San Francisco, CA 94105-1895

Paul D. Wilde  
ACTA, Inc.  
2790 Skypark Drive Suite 310  
Torrance, CA 90505-5345

Peter Yanev  
EQE Intl.  
44 Montgomery St. Suite 3200  
San Francisco, CA 94104

Rae Zimmerman  
Robert F. Wagner Graduate School of Public Service  
New York University  
4 Washington Square North  
New York, NY 10003-6671

1	MS 0127	John Cummings, 4512
1	MS 0151	Russell Skocypec, 9002
1	MS 0165	John D. German III, 12640
1	MS 0188	Cynthia Harvey, 4523
1	MS 0342	Dick Salzbrenner, 1805
1	MS 0367	Brian Damkroger, 1833
1	MS 0367	S. Jill Glass, 1833
1	MS 0367	Ed Beauchamp, 1833
1	MS 0437	Steve Attaway, 9117
1	MS 0439	Howard Walther, 9234
1	MS 0455	Laura Gilliom, 6232
1	MS 0481	Keith Ortiz, 2167
1	MS 0486	W. Richard Burcham, 2123
1	MS 0557	Randall Mayes, 9741
1	MS 0557	Todd Simmermacher, 9741
1	MS 0557	Tom Baca, 9741
1	MS 0724	Joan Woodard, 6000
1	MS 0736	Nestor Ortiz, 6400
1	MS 0744	Dennis Berry, 6403
1	MS 0744	Vince Luk, 6403
1	MS 0746	Robert Cranwell, 6411
20	MS 0751	Dale Preece, 6117
1	MS 0759	Mary Jane Hicks, 5845
20	MS 0782	Rudy Matalucci, 5848
1	MS 0782	Sharon O'Connor, 5848



1	MS 0769	Dennis Miyoshi, 5800
1	MS 0781	Dick Wayne, 5831
1	MS 0781	Ruth Duggan, 5831
1	MS 0782	Gordon Smith, 5848
1	MS 0828	Robert K. Thomas, 9104
1	MS 0827	John Brockmann, 9114
1	MS 0827	Richard Griffith, 9114
1	MS 0443	Harold S. Morgan, 9117
1	MS 0908	James Cox, 7832
1	MS 0933	Nenita Estes, 7823
1	MS 0933	Nick Winowich, 7823
1	MS 0937	Ricardo Ortiz, 7832
1	MS 0937	Tom Fatueros, 7935
1	MS 0939	John Milloy, 7900
1	MS 0957	William Sullivan, 1401
1	MS 1003	John Hurtado, 9611
1	MS 1231	Roger Hagengruber, 5000
1	MS 1351	Dominique Foley Wilson, 3613
2	MS 0899	Technical Library, 4916
2	MS 0619	Review/Approval Desk, 12690 for DOE/OSTI
1	MS 9018	Central Technical Files, 8940-2